

EC-1025

Enhanced 2U Server Chassis

SPECIFICATIONS

- 2U Height Rack-mount
- Equipped with Redundant ATX Power Supply, 300W with PFC function
- Input: 95 ~ 264VAC full range
- Output Rating
+3.3V/20A, +5V/32A, +12V/16A,
-5V/0.5A, -12V/0.8A, +5Vsb/1.5A

The current output of +3.3V and +5V shall not exceed 32A
Total +3.3V, +5V and 12V power not exceed 285W

- Supports Backplan: PCI-5SDA, PCI-6SDA, PX-6SDA, PCIAGP-5SD
- Hold-up time: 16ms min.
- Efficiency: 63% typical.
- Four Removable Hard Disk Drive Bay: Removable with aluminum housing for best cooling performance.
- IDE Interface HDD Bay: Supports ATA-100 interface
- SCSI Interface HDD Bay: Supports SCA HDD

- Supports standard 5.25" CD-ROM and 3.5" Floppy Disk Drive.
- Chassis color: Black (Pantone Black C)
- Operation Temperature: 0~50°C
- Depth: 618mm

ORDERING INFORMATION

- **EC-1025BSDR**
Enhanced 2U Server with 300W redundant power supply, SCA-2 HDD Drawer
- **EC-1025BIDR**
Enhanced 2U Server with 300W redundant power supply, two IDE channel for 4 HDD
- **EC-1025B4IDR**
Enhanced 2U Server with 300W redundant power supply, four IDE channel for 4 HDD
Note: EC-1025 without A78 LCD Module and A106 alarm board.



Equipped with 300W
Redundant Power Supply