

# PCISA-3716E2V PCISA Bus Socket-370SBC with Dual 10/100Mbps LAN, Audio, VGA

133MHz  
FSB

Tualatin  
Supports

## SPECIFICATIONS



Dual 10/  
100Mbps  
Ethernet

## ORDERING INFORMATION

- **PCISA-3716E2V**  
PCISA Socket-370 SBC with VGA,  
Audio & Dual Ethernet
- **PCISA-3716EV**  
PCISA Socket-370 SBC with VGA,  
Audio & Ethernet
- **CB-USB02** Dual ports USB cable  
with bracket

- **CPU:** Socket-370 66/100/133 MHz FSB Tualatin, P III/ Celeron™
- **System Chipset:** SiS630ET
- **System Memory:** One 168-pin DIMM sockets up to 512MB
- **Display:** – Integrated in SiS630ET Chipset
  - Bus: AGP 66MHz
  - V-RAM: Share with system memory up to 64MB RAM
  - Resolution: 1600 x 1200 (16-bit colors)
  - Connector: DB-15 for CRT display
- **Ethernet:** Dual Ethernet with one integrated in chipset and one Realtek 8100
- **SSD:** Support Compact Flash™ Type II Socket (rear side)
- **Audio :** AC'97 compliant Audio CODEC with 6W Amplifier
- **I/O:** – 2 x RS-232 serial port (16C550 UARTs compatible)
  - 1 x parallel port (SPP/EPP/ECP)
  - 2 x USB 1.1 (Pin header)
  - 1 x IrDA (SIR)
  - 1 x FDD port, support 1.44MB, 2.88MB, 3-mode function
  - 1 x ATA-100 IDE channels
- **WDT:** software programmable, support 1~ 255 sec. system reset
- **Support ATX power control function**
- **8 bit limited ISA (LPC-ISA)**
- **Power Consumption:** 5V@6A, 12V@170mA  
(Pentium® III 500MHz CPU and 512MB SDRAM)
- **Operating Temp:** 0°~60°C (CPU cooler required)
- **Relative Humidity:** 5~95%, non-condensing
- **GW:** 700g

**PCISA™**  
**BUS**