

# PCISA-3717EVT

PCISA bus Socket-370 SBC with  
LAN, Audio, Dual VGA or VGA & TV Output

Support Dual VGA Outputs or  
One VGA and One TV Output!!

**Tualatin  
Supports**

## SPECIFICATIONS



- **CPU:** Socket-370 66/100/133 MHz FSB Tualatin, P III/ Celeron™
- **System Chipset:** SiS630ST
- **System Memory:** One 168-pin DIMM sockets up to 512MB
- **Display:** – Integrated in SiS630ST Chipset
  - Bus: AGP 66MHz
  - V-RAM: Share with system memory up to 64MB RAM
  - Resolution: 1600 x 1200 (16-bit colors)
  - Connector: DB-15 for CRT display
  - TV output: support NTSC and PAL signal
- **Ethernet:** 1x onboard Realtek RTL8100 10/100 bps fast ethernet controller.
- **SSD:** Support Compact Flash™ Type II Socket (rear side)
- **Audio :** AC'97 compliant Audio CODEC
- **I/O:** – 2 x RS-232 serial port (16C550 UARTs compatible)
  - 1 x parallel port (SPP/EPP/ECP)
  - 2 x USB 1.1 (Pin header)
  - 1 x IrDA (SIR)
  - 1 x FDD port, support 1.44MB, 2.88MB, 3-mode function
  - 1 x ATA-100 IDE channels
- **Hardware monitoring system**
- **WDT:** software programmable, support 1~ 255 sec. system reset
- **Support ATX power control function**
- **8 bit limited ISA (LPC-ISA)**
- **Power Consumption:** 5V@6A, 12V @170mA (Pentium® III 500MHz CPU and 512MB SDRAM)
- **Interface:** PCISA golden edge with PCI & ISA (bus master limited performance)
- **Operating Temp:** 0°~60°C (CPU cooler required)
- **Relative Humidity:** 5~95%, non-condensing
- **GW:** 700g



VGA No.1




VGA No.2

or



VGA



TV

Best Solution for POS,  
Video Conference, Video  
on Demand Application!!

## ORDERING INFORMATION

- **PCISA-3717EVT** PCISA bus Socket-370 Base CPU Card with LAN, Audio, Dual VGA or VGA & TV Output
- **CB-USB02** Dual ports USB cable with bracket