

RACK-230A

1U Chassis

SPECIFICATIONS



RACK-230AW



The Internal Configuration

ACE-890 Series Power Supply

- 1U height 19" Rack mounting chassis
- Designed for full / half size CPU card
- Drive Bays : — 1 x 3.5" FDD
— 1 x 3.5" HDD
- Four 4cm cooling fans
- One USB port on front panel
- Supports backplane : PCI-2SD-R13, IP-2SD
- Supports one half size ISA or PCI add-on card
- Supports power supply : ACE-890 series power supply
- Vibration: 5~17Hz, 0.1" double amplitude displacement
17~640Hz, 1.5G acceleration peak to peak
- Shock: 10G acceleration peak to peak (11ms)
- Colors: Black (PANTONE Black C) or White (PANTONE 413C)
- Dimensions: 431(W) x 44(H) x 486(D)mm; (17" x 1.7" x 19.1")
- Net/GW (kg): 6/9

ORDERING INFORMATION

RACK-230A[C]/ACE-890A[B]: 1U rackmount chassis with ACE-890A power supply & B backplane

RACK-232

1U Chassis

SPECIFICATIONS

RACK-232W



RACK-232B



Install 3.5" HDD or Half-size Board

- 1U height 19" Rack mounting chassis
- Designed for full / half size CPU card
- Drive Bays: — 1 x 3.5" FDD
— 1 x 5.25" Drive
— 1 x 2.5" HDD (With Anti-Shock designed)
— 1 x 3.5" HDD (Share with add-on card space)
- Four 4cm cooling fans
- One USB port on front panel
- Supports backplane: PCI-2SD-R13, IP-2SD
- Supports one half size ISA or PCI add-on card, share with one 3.5" HDD space
- Supports power supply: ACE-890 series power supply
- Vibration : 5~17Hz, 0.1" double amplitude displacement
17~640Hz, 1.5G acceleration peak to peak
- Shock: 10G acceleration peak to peak (11ms)
- Colors: Black (PANTONE Black C) or White (PANTONE 413C)
- Dimensions: 431(W) x 44(H) x 488(D)mm; (17" x 1.7" x 19.2")
- Net/GW (kg): 6/9

ORDERING INFORMATION

RACK-232[C]/ACE-890A[B]: 1U rackmount chassis with ACE-890A power supply & B backplane

RACK-235

1.5U Chassis

SPECIFICATIONS



RACK-235W

RACK-235B

PCI-4SD



PCI-4SD2



- 1.5U height 19" Rack mounting chassis
- Drive Bays: — 1 x 3.5" FDD
— 2 x 3.5" HDD
- Two 6cm cooling fans with filter
- Standard equipped with PCI-4SD backplane
- Supports PICMG bus full size CPU card
- Supports backplane: — PCI-4SD: 1xPICMG, 1xISA & 2xPCI
— PCI-4SD2: 1xPICMG, 3xPCI
- Supports power supply: ACE-890 series power supply
- Vibration: 5~17Hz, 0.1" double amplitude displacement
17~640Hz, 1.5G acceleration peak to peak
- Shock: 10G acceleration peak to peak (11ms)
- Colors: Black (PANTONE Black C) or White (PANTONE 413C)
- Dimensions: 431(W) x 65(H) x 486(D)mm; (17" x 2.6" x 19.1")
- Net/GW (kg): 6/10



ORDERING INFORMATION

RACK-235[C]/ACE-890A/PCI-4SD : 1.5U rackmount chassis with ACE-890A power supply & PCI-4SD backplane