

RACK-232 1U Chassis

RACK-232W



RACK-232B



Install 3.5" HDD or
Half-size Board

SPECIFICATIONS

- **1U height 19" Rack mounting chassis**
- **Designed for full / half size CPU card**
- **Drive Bays:** — 1 x 3.5" FDD
— 1 x 5.25" Drive
— 1 x 2.5" HDD (With Anti-Shock designed)
— 1 x 3.5" HDD (Share with add-on card space)
- **Four 4cm cooling fans**
- **One USB port on front panel**
- **Supports backplane:** PCI-2SD-R13, IP-2SD
- **Supports one half size ISA or PCI add-on card, share with one 3.5" HDD space**
- **Supports power supply:** ACE-890 series power supply
- **Vibration :** 5~17Hz, 0.1" double amplitude displacement
17~640Hz, 1.5G acceleration peak to peak
- **Shock:** 10G acceleration peak to peak (11ms)
- **Colors:** Black (PANTONE Black C) or White (PANTONE 413C)
- **Dimensions:** 431(W) x 44(H) x 488(D)mm; (17" x 1.7" x 19.2")
- **Net/GW (kg):** 6/9

ORDERING INFORMATION

RACK-232[C]/ACE-890A/[B]: 1U rackmount chassis with ACE-890A power supply & [B] backplane

RACK-235 1.5U Chassis

RACK-235W



RACK-235B

PCI-4SD



PCI-4SD2



SPECIFICATIONS

- **1.5U height 19" Rack mounting chassis**
- **Drive Bays:** — 1 x 3.5" FDD
— 2 x 3.5" HDD
- **Two 6cm cooling fans with filter**
- **Standard equipped with PCI-4SD backplane**
- **Supports PICMG bus full size CPU card**
- **Supports backplane:** — PCI-4SD: 1xPICMG, 1xISA & 2xPCI
— PCI-4SD2: 1xPICMG, 3xPCI
- **Supports power supply:** ACE-890 series power supply
- **Vibration:** 5~17Hz, 0.1" double amplitude displacement
17~640Hz, 1.5G acceleration peak to peak
- **Shock:** 10G acceleration peak to peak (11ms)
- **Colors:** Black (PANTONE Black C) or White (PANTONE 413C)
- **Dimensions:** 431(W) x 65(H) x 486(D)mm; (17" x 2.6" x 19.1")
- **Net/GW (kg):** 6/10

**Most Compact
design for 4
slots in 1.5U
chassis**

ORDERING INFORMATION

RACK-235[C]/ACE-890A/PCI-4SD : 1.5U rackmount chassis with ACE-890A power supply & PCI-4SD backplane