

RACK-3030

6U Height 20-Slot Full Size Industrial PC Chassis
With Redundant Power Supply



RACK-3030W
With 4 x 5.25"
Drive Bay



RACK-3030W
Tower Stand

Two 5.25" Drive or
Four 3.25" Drive



ARH-6400F
400W ATX Redundant
Power Supply

Best System
Cooling Performance
for IT Application!!



RACK-3030B



Rear View

400W AT/ATX
Power Supply



Internal View

Features:

- 6U height
- Supports redundant power supply
- Four reset switches and PS/2 type KBD connectors for quad system applications
- Four 9cm cooling fans with filter
- Designed with easy removal of the driver bay

Ordering Information:

RACK-3030 C/ACE-940AP:

6U 20-slot rackmount chassis with ACE-940AP power supply

RACK-3030R C/ARH-6400F:

6U 20-slot rackmount chassis with 400W ATX type redundant power supply

RACK-3030 C/ATX /ACE-840AP:

6U ATX Main board rackmount chassis with ACE-840AP power supply

C Color Code : B = Black; W = White

SLIDE-18 :

18" Sliding

SLIDE-24 :

24" Sliding

EXTENDER-6 :

6" extender for 18" or 24" slides

NEW

Specifications

- 6U height 19" Rack mounting chassis
- Four reset switches and PS/2 type KBD connectors for quad system applications
- Drive Bays :
 - 7 x 3.5" HDD
 - 2 x 5.25" Drive Bays
- Four 9cm cooling fans with filter on the front panel and two 6cm fans on the both side
- Built-in fan speed sensors board to detect fans speed
- Designed with anti-vibration card clamp to keep system stable
- Supports backplane : BP-20S, BP-20SD, BP-20ST, BP-20SQ, IP-19S, IP-18SD, PCI-19S, PCI-18SD, PCI-17SQ, PX-19S, PX-20S, PX-20S2, PXAGP-19S, PXAGP-19S2
- Supports PS/2 size power supply or 400W redundant AT/ATX power supply
- Optional Slides: 24" or 18"
- Vibration : 5~17Hz, 0.1" double amplitude displacement
17~640Hz, 1.5G acceleration peak to peak
- Shock: 10G acceleration peak to peak (11ms)
- Colors: Black (PANTONE Black C) or White (PANTONE 413C)
- Dimensions: 431(W) x 266.6(H) x 516.7(D)mm;
(17" x 10.5" x 20.3")
- Net/GW (kg): 19/26

Dimensions:

